

# Halogen FastFit

## Hi-Brite 7016G 1200W 80V FastFit.

Halogen FastFit lamps are replaced in seconds - thanks to the specially designed base. The compact filament ensures high beam intensity, while the shock-resistant design allows easy handling and reliable use in moving head systems. In addition, the highly innovative P3 technology allows use at higher temperatures, which further extends lifetime and consistency of light output. P3 technology also allows the lamp to be used in any burning position and enables more compact designs of fixtures. And because the FastFit design is also applied to Philips MSR/MSD Gold™ lamps, switching lamp technologies is also quick and easy.

#### Product data

#### • General Characteristics

Philips Code 7016G ANSI Code

P3 Technology System Description Cap-Base PGJX50 **Bulb Finish** Clear Filament Shape Bi-Plane Operating Position any Main Application Entertainment

Life to 50% failures 200 hr

## • Light Technical Characteristics

Color Temperature 3250 K

**Technical** 

Luminous Flux Lamp 36000 Lm

## • Electrical Characteristics

Lamp Wattage 1200 W Voltage 80 V Dimmable Yes Rapid Acting HBC 16 V Fuse

# • Luminaire Design Requirements

Pinch Temperature 500 (max) C

## • Product Dimensions

Overall Length C 140 (max) mm Diameter D 25 (max) mm Overall Width E 41 (max) mm Light Center Length 82 mm

Filament Dimensions 12x10.5 (WxH) [mm] Filament Height H 10.5 mm Filament Length W 11.7 mm

### • Product Data

924575228928 Order code 924575228928 Full product code

Full product name Hi-Brite 7016G 1200W 80V FastFit Order product name Hi-Brite 7016G 1200W 80V FastFit

Pieces per pack 10 Packing configuration Packs per outerbox 10

Bar code on pack -8711500507075

EAN1

8711500507082 Bar code on outerbox - EAN3


924575228928 Logistic code(s) -

12NC

Net weight per piece 0.139 kg




# Dimensional drawing



## Hi-Brite 7016G 1200W 80V FastFit

Product	C (Max)	D (Max)	E (Max)	H (Norm)	L (Norm)	W (Norm)
Hi-Brite 7016G 1200W PGJX50 80V FastFit	140	25	41	10.5	82	11.7



PGJX50



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.