

## Halogen FastFit

## 7018G 800W 230V FastFit

Halogen FastFit lamps are replaced in seconds - thanks to the specially designed base. The compact filament ensures high beam intensity, while the shock-resistant design allows easy handling and reliable use in moving head systems. In addition, the highly innovative P3 technology allows use at higher temperatures, which further extends lifetime and consistency of light output. P3 technology also allows the lamp to be used in any burning position and enables more compact designs of fixtures. And because the FastFit design is also applied to Philips MSR/MSD Gold™ lamps, switching lamp technologies is also quick and easy.

## Product data

#### General Characteristics

| Philips Code<br>ANSI Code<br>System Description<br>Cap-Base<br>Bulb Finish<br>Filament Shape<br>Operating Position | 7018G<br>GRT<br>P3 Technology<br>PGJX50<br>Clear<br>Bi-Plane<br>any<br>Entertainment |
|--|--|
| Main Application   | Entertainment  |
| Life to 50% failures   | 150 hr   |

#### • Light Technical Characteristics

| Color Temperature  | 3200 K   |
|--------------------|----------|
| Technical          |          |
| Luminous Flux Lamp | 20000 Lm |

#### • Electrical Characteristics

| Lamp Wattage     | 800 W |
|------------------|-------|
| Voltage          | 230 V |
| Dimmable         | Yes   |
| Rapid Acting HBC | 6.3 V |
| Fuse             |       |

#### • Luminaire Design Requirements

Pinch Temperature 500 (max) C

#### Product Dimensions

| Overall Length C<br>Diameter D |
|--------------------------------|
| Overall Width E                |
| Light Center Length            |
|                                |
| –<br>Filament Dimensions       |
| (WxH) [mm]                     |
| Filament Height H              |
| Filament Length W              |

#### • Product Data

Order code Full product code Full product name Order product name Pieces per pack Packing configuration Packs per outerbox Bar code on pack -EAN1 Bar code on outerbox - EAN3 Logistic code(s) -12NC Net weight per piece


140 (max) mm 19 (max) mm 41 (max) mm 79 mm 9x12.5 12.5 mm 9 mm

924582344228 924582344228 7018G 800W 230V FastFit 7018G 800W 230V FastFit 1 10 8727900807370 8727900807387 924582344228 0.130 kg

# PHILIPS


## Halogen FastFit

## Dimensional drawing



#### 7018G 800W 230V FastFit

| Product                 | C (Max) | D (Max) | E (Max) | H (Norm) | L (Norm) | W (Norm) |
|-------------------------|---------|---------|---------|----------|----------|----------|
| 7018G 800W 230V FastFit | 140     | 19      | 41      | 12.5     | 79       | 9        |



PGJX50



© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting