

UV-B Narrowband PL-L/PL-S

PL-L 36W/01/4P 1CT

More than 400 independent clinical studies have proven that the UVB Narrowband PL-L/PL-S lamps are safer and more effective than any other lamps in their class. The PL-L/PL-S versions provide additional design freedom for system manufacturers since these are space-saving compact, single-ended lamps. Further flexibility is assured since they use the same lamp caps as general lighting lamps, they also use the same universal ballasts. Their best-in-class treatment effectiveness is a result of their very narrow waveband emission: between 305 and 315 nm with a peak at 311 nm. This is the most efficacious waveband for the treatment of psoriasis, and is therefore much more focused. As a result, exposure times are much shorter and this in turn leads to a reduction of side effects such as reddening of the skin and itching. All of this makes them ideal for phototherapy treatment of diseases such as psoriasis and vitiligo. What's more, because the overall dosage of this narrowband radiation can be closely controlled, these lamps are suitable for home therapy.

Product data

General Characteristics

Cap-Base	2G11
Cap-Base Information	4 Pins
Bulb	2xT16
Main Application	Phototherapy
Useful Life	1000 hr
Life to 50% failures	1000 hr
EL	

• Light Technical Characteristics

Color Code Chromaticity Coor-	01 228 -
dinate X Chromaticity Coor- dinate Y	230 -
Depreciation 500	15 %
Depreciation 1000 hours	20 %

• Electrical Characteristics

Lamp Wattage	36 W
Lamp Wattage Tech-	36 W
nical	
Lamp Voltage	105 V
Lamp Current	0.435 A

• UV-related Characteristics

UV-B Radiation	4.8 W
100hr (IEC)	

UV-B Radiation 5hr 6.2 W (IEC)

• Product Dimensions

Base Face to Base Face A Insertion Length B Overall Length C Diameter D Diameter D1

410 (max) mm 416.6 (max) mm 39 (max) mm

18 (max) mm

384.2 (max) mm

• Product Data

Order code	,
Full product code	,
Full product name	
Order product name	
Pieces per pack	
Packing configuration	
Packs per outerbox	
Bar code on pack -	1
EAN1	
Bar code on	1
outerbox - EAN3	
Logistic code(s) -	,
12NC	
Net weight per piece	


927903400121 927903400121 PL-L 36W/01/4P 1CT PL-L 36W/01/4P 1CT/25 1 25 25 8711500868893 8711500868909

927903400121

er piece 104.000 gr




Dimensional drawing




PL-L	36W/01/4P 1CT	

Product	A (Max)	B (Max)	C (Max)	D (Max)	D1 (Max)
PL-L 36W/01/4P	384.2	410	416.6	39	18



2G11

Photometric data





© 2014 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting