

Flexo Print

TL 140W/03

Flexo print TL lamps emit almost all of their light (99.9%) in the useful UVA and visible blue wavebands – between 350 and 400 nm – and have peak intensity at 370 nm (except for the /03 version). This makes them ideal for flexo printing equipment and photopolymerization processes. In addition, the 'R' lamps in the family have an internal 200-degree reflector to further optimize the lamp's overall efficiency.

Product data

• General Characteristics

Cap-Base G13
Bulb T38
Main Application Reprography
Useful Life 3000 hr
Life to 50% failures 5000 hr
EM

-- -

• Light Technical Characteristics

Color Code Color Designation	03 Super Actinic
(text) Chromaticity Coor-	175 -
dinate X	
Chromaticity Coor-	45 -
dinate Y	
Depreciation 500	20 %
hours	
Depreciation 1000	30 %
hours	
Depreciation 2000	40 %
hours	

• Electrical Characteristics

Lamp Wattage	140 W
Lamp Wattage Tech-	142 W
nical	
Lamp Voltage	118 V
Lamp Current	1.46 A
Mains Voltage Stable	30.4 W
Operation	

• UV-related Characteristics

UV-A Radiation 1.00 W 100hr (IEC)

• Product Dimensions

Base Face to Base Face A Insertion Length B Overall Length C Diameter D 1500 (max) mm 1504.7 (min), 1507.1 (max) mm 40.5 (max) mm

928012700303 928012700303

Product Data Order code

Full product code


TL 140W/03 Full product name Order product name TL 140W/03 Pieces per pack Packing configuration 25 Packs per outerbox 25 8711500720948 Bar code on pack -EAN1 8711500720955 Bar code on outerbox - EAN3 928012700303 Logistic code(s) -12NC Net weight per piece 331.000 gr



Dimensional drawing

TL 140W/03


Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL 140W/03	1500	1504.7	1507.1	1514.2	40.5






G13

Photometric data







Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.