

MSR Gold™ FastFit

MSR Gold™ 2000 FastFit 1CT

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR GoldTM 1200 FastFit can be operated in a lamp wattage range between 800W and 1400W.

Product data

• General Characteristics

System Description FastFit Cap-Base PGJX50 Cap-Base Information PGJX50 Execution Operating Position

Entertainment Main Application

Life to 50% failures 750 hr

• Light Technical Characteristics

Color Code Color Rendering 91 Ra8 Index

Color Temperature 6050 K Color Temperature 6050 K

Technical 321 -Chromaticity Coor-

dinate X Chromaticity Coor-

332 dinate Y

Luminous Flux Lamp

154000 (min), 162000 (nom) Lm EM

81 Lm/W Luminous Efficacy

Lamp EM

• Electrical Characteristics

2000 W Lamp Wattage Lamp Wattage Tech-2000 W nical

Lamp Current 15.2 A 198 (min) V Ignition Supply

Voltage

Dimmable

· Luminaire Design Requirements

Pinch Temperature 500 (max) C **Bulb Temperature** 950 (max) C

• Product Dimensions

Overall Length C 134 (max) mm 34 (max) mm Diameter D Width F 50 mm

66 (min), 67 (nom), 68 (max) mm Light Center Length

Yes

Arc Length O 8.0 mm

• Product Data

Order code 928176905114 928176905114 Full product code

MSR Gold™ 2000 FastFit 1CT Full product name MSR Gold 2000 FastFit 1CT/8 Order product name

Pieces per pack Packing configuration Packs per outerbox

8727900919493 Bar code on pack -

EAN1

8727900919509 Bar code on outerbox - EAN3


Logistic code(s) -928176905114

12NC

Net weight per piece 0.147 kg



Dimensional drawing



MSR Gold™ 2000 FastFit 1CT

Product	A (Min)	A (Norm)	A (Max)	C (Max)	D (Max)	D1 (Norm)	F (Min)	F (Norm)	F (Max)	L (Min)	L (Norm)	L (Max)	O (Norm)
MSR GOLD 2000W FastFit	t -	-	=	134	34	=	-	50	-	66	67	68	8.0



PGJX50



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.