

MASTER TL5 Circular

MASTER TL5 Circular 22W/830 1CT/10

This circular TL5 lamp (tube diameter 16 mm) offers extended design possibilities. The slim tube allows the creation of extremely flat luminaires and enables omnidirectional light distribution. It is suitable for a wide range of professional and semi-professional applications, and is ideal for use in shops, offices and public areas with unconventional layouts.

Product data

• General Information

Cap-Base 2GX13 [2GX13] Life To 50% Failures 12000 h Preheat (Nom)

• Light Technical

Color Code 830 [CCT of 3000K] Luminous Flux 1800 lm (Nom) Luminous Flux 1800 lm (Rated) (Nom) Color Designation Warm White (WW) Chromaticity Coor-440 dinate X (Nom) Chromaticity Coor-403 dinate Y (Nom) Correlated Color 3000 K Temperature (Nom) 82 lm/W Luminous Efficacy (rated) (Nom) Color Rendering Index (Max) Color Rendering 80 Index (Min) Color Rendering 85 Index (Nom)

Operating and Electrical

Power (Rated) 22.3 W (Nom)

Lamp Current (Nom) 0.300 A

• Temperature

Design Temperature 35 °C (Nom)

Controls and Dimming

Dimmable Yes

• Approval and Application

Energy Efficiency A
Label (EEL)
Mercury (Hg) 2.5 mg
Content (Nom)

• Product Data

871150064095625 Full product code MASTER TL5 Circular 22W/830 Order product name 1CT/10 EAN/UPC - Product 8711500640956 Order code 927965083013 Numerator - Quantity Per Pack Numerator - Packs 10 per outer box Material Nr. (12NC) 927965083013 45.000 g FSCH-22/30/1B-L/P-2GX13-16 Net Weight (Piece) ILCOS Code




MASTER TL5 Circular

Warnings and Safety

• A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and


remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Dimensional drawing





TL5-C 22W/830

| Product | D | D | E | E | I | 1 |
|------------------------------------|-------|-------|--------|--------|--------|--------|
| MASTER TL5 Circular 22W/830 1CT/10 | 18 mm | 14 mm | 220 mm | 230 mm | 187 mm | 197 mm |



Photometric data







Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.