MASTER LEDtube InstantFit HF

MASTER LEDtube HF 1200mm UO 21W830 T8

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. The MASTER LEDtube Performance is the ideal solution for customers which have higher light requirements and the want to maximize value over lifetime.(need the longest lifetime). Full energy savings and TCO benefits.

Product data

General Information

PHILIPS

Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Main Application	Industrial
Nominal Lifetime	50000 h
(Nom) Switching Cycle B50L70	50000× 50000

• Light Technical

Color Code Beam Angle (Nom) Luminous Flux	830 160 230
(Nom) Luminous Flux	230
(Rated) (Nom)	
Rated Beam Angle	160
Correlated Color	300
Temperature (Nom)	
Color Consistency	6 st
Color Rendering	83
Index (Nom)	
Llmf At End Of	70 %
Nominal Lifetime	
(Nom)	

• Operating and Electrical

Input Frequency Power (Rated) (Nom)	25000/80000 Hz 21 W
Lamp Current (Nom)	400 A
Starting Time (Max)	0.5 s
Warm Up Time To 60% Light (Max)	0.1 s
Power Factor (Min)	0.9
Voltage (Nom)	50-100 ∨

) [CCT of 3000K]
00 lm
00 lm
) ° 00 K
teps
%

• Temperature

T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum	45 °C
(Nom)	

· Controls and Dimming

Dimmable No

• Mechanical and Housing

Product Length 1200 mm

> Yes No A+

Approval and Application

Energy Saving	
Product	
Suitable For Accent	
Lighting	
Energy Efficiency	
Label (EEL)	
Approval Marks	

CE marking KEMA Keur certificate **RoHS** compliance VDE marking

• Product Data Full product code

Order product name

EAN/UPC - Product

871869655282700 MASTER LEDtube HF 1200mm UO 21W830 T8 8718696552827




MASTER LEDtube InstantFit HF

Order code Numerator - Quan-	929001211302 1
tity Per Pack	
Numerator - Packs	10
per outer box	

Material Nr. (12NC) Net Weight (Piece)

VC) 929001211302 (e) 0.360 kg

Dimensional drawing



TLED 50-100V 20W-36W 2500Im 3000K G13 ND

Product	D1	D2	A1	A2	A3
MASTER LEDtube HF 1200mm UO	25.68 mm	28 mm	1198.0 mm	1205.0 mm	1212.0 mm
21W830 T8					



 $\textcircled{\sc c}$ 2016 Koninklijke Philips N.V. (Royal Philips) All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting