





BL




BL-EVG



BL-118H-EVG  
BL-218H-EVG  
BL-136H-EVG



BL-236H-EVG  
BL-258H-EVG  
BL-158H-EVG



BL-418H-EVG  
BL-3-4x14H-EVG

Kanlux		In	[W]
BL-118H-EVG	5905339704801	0,08A	1 x 18
BL-136H-EVG	5905339704818	0,16A	1 x 36
BL-158H-EVG	5905339704825	0,26A	1 x 58
BL-218H-EVG	5905339704832	0,16A	2 x 18
BL-236H-EVG	5905339704849	0,32A	2 x 36
BL-258H-EVG	5905339704856	0,51A	2 x 58
BL-418H-EVG	5905339704863	0,98A	4 x 18
BL-3-4x14H-EVG	5905339082404	0,19A / 0,24A	3 x 14 / 4 x 14

220-240V~  
50/60Hz

EEI=A2



PF(λ)  
0,98

U<sub>max</sub> (V)  
<450

mm  
0,5-1,5

IP  
20



°C  
max 50



ERC

CE

CZ

stříbrný  
těleso: ocelový plech

model BL-3-4x14H-EVG slouží ke stabilizaci proudu zářivek T5, ostatní modely slouží ke stabilizaci proudu zářivek T8

SK

strieborný  
teleso: ocelový plech

model BL-3-4x14H-EVG slúži k stabilizácii prúdu žiaroviek T5, ostatné modely slúžia k stabilizácii prúdu žiaroviek T8

HU

ezüst  
ház: acéllemez

a BL-3-4x14H-EVG modell T5 fénycsövek működ-tetésére való, a többi modell T8 fénycsövek működ-tetésére való