



MASTER LEDtube EM/ Mains

MASTER LEDtube EM/ Mains

MAS LEDtube 1200mm UO 18W 865 T8 RN

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. For those that are looking for value for money within limited budget and re-lamping efforts for better light effect and lifetime. The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. For those that are looking for value for money within limited budget and re-lamping efforts for better light effect and lifetime.

Product data

• General Information

Cap-Base	G13 [G13 Medium Bi-Pin Fluorescent]
Main Application	Industrial
Nominal Lifetime (Nom)	50000 h
Switching Cycle B50L70	200000X 50000

• Light Technical

Color Code	865 [CCT of 6500K]
Beam Angle (Nom)	160 °
Luminous Flux (Nom)	2500 lm
Luminous Flux (Rated) (Nom)	2500 lm
Rated Beam Angle	160 °
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	139 lm/W
Color Consistency	6 steps
Color Rendering Index (Nom)	83

LLMF At End Of Nominal Lifetime (Nom)	70 %
---------------------------------------	------

• Operating and Electrical

Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	18 W
Lamp Current (Max)	82 mA
Lamp Current (Min)	75 mA
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.1 s
Power Factor (Nom)	0.9
Voltage (Nom)	220-240 V

• Temperature

T-Ambient (Max)	35 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	55 °C

PHILIPS

MASTER LEDtube EM/Mains

• Controls and Dimming

Dimmable No

• Mechanical and Housing

Product Length 1200 mm

• Approval and Application

Energy Saving Product Yes
 Suitable For Accent Lighting No
 Energy Efficiency Label (EEL) A++
 Approval Marks CE marking
 KEMA Keur certificate

Energy Consumption kWh/1000 h
 RoHS compliance 18 kWh

• Product Data

Full product code 871869656531500
 Order product name MAS LEDtube 1200mm UO 18W 865 T8 RN
 EAN/UPC - Product 8718696565315
 Order code 929001222102
 Numerator - Quantity Per Pack 1
 Numerator - Packs per outer box 10
 Material Nr. (12NC) 929001222102
 Net Weight (Piece) 0.270 kg


Warnings and Safety

• NOTES: The overall energy efficiency and light distribution of any installation that uses these lamps are determined by the design of the installation.

Warnings and Safety

• NOTES: The overall energy efficiency and light distribution of any installation that uses these lamps are determined by the design of the installation.


Dimensional drawing




TLED 4ft 220-240V 18W-36W 6500K G13 ND

Product	D1	D2	A1	A2	A3
MAS LEDtube 1200mm UO 18W 865 T8 RN	25.78 mm	28 mm	588.6 mm	1205.3 mm	1212.4 mm

Photometric data





© 2016 Philips Lighting Holding B.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2016, June 7
data subject to change